

SECTION 1: Identification**1.1. Identification**

Product form : Mixture
Product name : FOAMING SEALER
Product code : RP-FS

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Sky Blue Chemical
760 W. Exchange Road
Ogden, Utah 84401 - USA
T (800) 998-2808
www.skybluechemical.com

1.4. Emergency telephone number

Emergency number : Chemtrec 1-800-424-9300

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS US classification**

Eye Dam. 1 Causes serious eye damage
Aquatic Acute 3 Harmful to aquatic life
Aquatic Chronic 3 Harmful to aquatic life with long lasting effects

2.2. GHS Label elements, including precautionary statements**GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

Causes serious eye damage
Harmful to aquatic life
Harmful to aquatic life with long lasting effects

Precautionary statements (GHS US) :

Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection/face protection.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center or doctor.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

FOAMING SEALER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
butyl glycoether	(CAS-No.) 111-76-2	5 – 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2B, H320
HUE METANIL CONC LIQUID (colorants)		5 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H302 Eye Irrit. 2B, H320 Aquatic Acute 2, H401 Aquatic Chronic 4, H413
JUICY MANGO (Fragrance)		5 – 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Lauryldimethylamine oxide	(CAS-No.) 1643-20-5	3 – 5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Isopropyl alcohol	(CAS-No.) 67-63-0	0.1 – 3	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
- First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after eye contact : Serious damage to eyes.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

- Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.

FOAMING SEALER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

FOAMING SEALER	
No additional information available	
Lauryldimethylamine oxide (1643-20-5)	
No additional information available	
butyl glycolether (111-76-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	Eye & URT irr
USA - OSHA - Occupational Exposure Limits	
Local name	2-Butoxyethanol
OSHA PEL (TWA) (mg/m ³)	240 mg/m ³
OSHA PEL (TWA) (ppm)	50 ppm
Isopropyl alcohol (67-63-0)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Propanol
ACGIH TWA (ppm)	200 ppm
ACGIH STEL (ppm)	400 ppm
Remark (ACGIH)	Eye & URT irr; CNS impair
USA - OSHA - Occupational Exposure Limits	
Local name	Isopropyl alcohol
OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
OSHA PEL (TWA) (ppm)	400 ppm
HUE METANIL CONC LIQUID	
No additional information available	
JUICY MANGO	
No additional information available	

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

FOAMING SEALER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: 6 – 8
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 212 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 8.93 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

FOAMING SEALER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Lauryldimethylamine oxide (1643-20-5)	
LD50 oral rat	1064 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))

butyl glycolether (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
LC50 Inhalation - Rat	> 4.26 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

Isopropyl alcohol (67-63-0)	
LD50 oral rat	5840 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	16400 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat [ppm]	> 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

HUE METANIL CONC LIQUID	
LD50 oral rat	> 3000 mg/kg
LD50 dermal rat	> 2 g/kg

Skin corrosion/irritation : Not classified
pH: 6 – 8
Serious eye damage/irritation : Causes serious eye damage.
pH: 6 – 8
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

butyl glycolether (111-76-2)	
IARC group	3 - Not classifiable

Isopropyl alcohol (67-63-0)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

Isopropyl alcohol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified
Viscosity, kinematic : No data available

FOAMING SEALER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after eye contact : Serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Lauryldimethylamine oxide (1643-20-5)	
LC50 fish 1	134 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value)
EC50 Daphnia 1	3.9 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
butyl glycoether (111-76-2)	
LC50 fish 1	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	911 mg/l (72 Hr.)
Isopropyl alcohol (67-63-0)	
LC50 fish 1	9640 – 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)

12.2. Persistence and degradability

Lauryldimethylamine oxide (1643-20-5)	
Persistence and degradability	Readily biodegradable in water.
butyl glycoether (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O ₂ /g substance
Chemical oxygen demand (COD)	2.2 g O ₂ /g substance
ThOD	2.305 g O ₂ /g substance
BOD (% of ThOD)	0.31
Isopropyl alcohol (67-63-0)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.19 g O ₂ /g substance
Chemical oxygen demand (COD)	2.23 g O ₂ /g substance
ThOD	2.4 g O ₂ /g substance

12.3. Bioaccumulative potential

Lauryldimethylamine oxide (1643-20-5)	
Partition coefficient n-octanol/water (Log Pow)	< 2.7 (Calculated)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
butyl glycoether (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value; BASF test; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Isopropyl alcohol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

Lauryldimethylamine oxide (1643-20-5)	
Ecology - soil	Low potential for adsorption in soil.
butyl glycoether (111-76-2)	
Surface tension	0.027 N/m (25 °C)

FOAMING SEALER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycoether (111-76-2)	
Partition coefficient n-octanol/water (Log Koc)	0.451 – 0.882 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
Isopropyl alcohol (67-63-0)	
Surface tension	No data available (test not performed)
Partition coefficient n-octanol/water (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

Transportation of Dangerous Goods

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed as Active, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Quaternary Ammonium Compounds	CAS-No. Not Available	5 – 10%
HUE METANIL CONC LIQUID	CAS-No.	5 – 10%
JUICY MANGO	CAS-No.	5 – 10%
Polysorbate 20	CAS-No.	0.1 – 1%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

ethylene glycol	CAS-No. 107-21-1	< 0.1%
Isopropyl alcohol	CAS-No. 67-63-0	0.1 – 3%
Methyl alcohol	CAS-No. 67-56-1	< 0.1%
Chloromethane	CAS-No. 74-87-3	< 0.1%

butyl glycoether (111-76-2)

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	---

ethylene glycol (107-21-1)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	5000 lb
-----------	---------

FOAMING SEALER


Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetic acid (64-19-7)	
CERCLA RQ	5000 lb
Glycidyloxypropyl trimethoxysilane (2530-83-8)	
EPA TSCA Regulatory Flag	TP - TP - indicates a substance that is the subject of a proposed TSCA section 4 test rule.
Methyl alcohol (67-56-1)	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	5000 lb
Chloromethane (74-87-3)	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	100 lb

15.2. International regulations

15.3. US State regulations

 **WARNING:** This product can expose you to ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Glycerol(56-81-5)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
butyl glycolether(111-76-2)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
ethylene glycol(107-21-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Isopropyl alcohol(67-63-0)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Acetic acid (64-19-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Methyl alcohol(67-56-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List
Chloromethane(74-87-3)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 11/03/2021

FOAMING SEALER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment - Chronic Hazard Category 4
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis

SDS US (GHS HazCom 2012)

The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.